



Esko Rechargeable LED Beacon

Operating Instructions

- 1. Battery Status Display
- 2. ON/OFF Switch / Function Switch
- 3. Charging Port
- 4. Magnetic Base





To change flash pattern, with beacon operating press and hold on/off switch for 5 seconds

- Light source: 12 x 3W 3535 high power LEDs
- 3 flash patterns—single flash, dual flash, rotate
- Integral on/off switch and smart battery status LED indicator
- E-approved to ECE R65 when running from external power
- Battery: 18650 li-ion battery, 7.4V/2200MA
- Charging voltage: 12-24V DC or 240V AC

- Charging Time: 3 hours
- Run time: 3 hours
- Waterproof rating: IP65
- Mounting: Combined magnet and suction cup
- Size: 140mm (h), 128 mm (dia)
- Charging cable stretches to maximum length of 3
 metres
- Not for high speed operation. 100kmh max vehicle speed.

Charges from DC 12-24V and AC 240V are supplied. Supplied with 240V adapter and 12-24V cigarette plug



Fully charge the battery before use. Charge the battery every 6 months if not in use. Run time can vary from 3 hours to 4 hours depending on flash pattern, ensure that the battery is sufficiently charged to maintain run time at all times when the beacon is expected to be operating. If internal battery is low the beacon can be externally powered using the cigarette lighter cable.

Supplied by: Esko Safety 56 Hurlstone Drive New Plymouth 4312 New Zealand T 0800 500 470

www.eskosafety.com

