

# esko®

# NIGHTSTICK®

Life Depends on Light™

Operates as a flashlight, a floodlight, or a Dual-Light™ (both the flashlight and floodlight on at the same time)

Flashlight setting offers 3 user-selectable brightness settings of 200/100/60 Lumens plus a strobe feature with a 267m beam distance

High-efficiency deep parabolic reflector flashlight mode is perfect for cutting through smoke and lighting up objects at great distances



## NIGHTSTICK RIGHT ANGLE LED RECHARGEABLE TORCH

EIT-RARR

Nightstick Intrinsically Safe Dual-Light™ right-angle light—rechargeable



3 User-selectable brightness settings on the flashlight including a 20 Lumen Survival Mode, plus a strobe



FL STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	200 LUMENS	200 LUMENS	100 LUMENS	60 LUMENS
	8h	6h	11h	22h
	235m	267m	199m	145m
	13836cd	22249cd	14828cd	7790cd
	2m			1m



### PERFORMANCE FEATURES

- + Operates as a flashlight, a floodlight, or a Dual-Light™ (both the flashlight and floodlight on at the same time)
- + Flashlight setting offers 3 user-selectable brightness settings of 200/100/60 Lumens plus a strobe feature with a 267m beam distance
- + High-efficiency deep parabolic reflector flashlight mode is perfect for cutting through smoke and lighting up objects at great distances
- + Floodlight setting offers 3 user-selectable brightness settings of 200/100/20 Lumen
- + 20 Lumen 'Survival Mode' provides just enough light in emergency situations with a run-time of 3½ days
- + Run-time: flashlight high-6 hours, medium-11½ hours, low-22½ hours, floodlight high-6 hours, medium-11½ hours, survival-40 hours, Dual-Light™-6 hours
- + cULus and MSHA certified Intrinsically Safe Permissible

- + CREE® LED technology, 50,000+ hours LED life
- + 3 User-selectable brightness settings on the flashlight including a 20 Lumen Survival Mode, plus a strobe
- + Powered by rechargeable Lithium-ion battery pack (included)
- + Recharge time is 6 hours
- + Battery charge status indicator (for use only with rechargeable battery)
- + Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)
- + Charger meets requirements of NFPA-1901 (2009) mounted in any position
- + IP-X7 waterproof rated
- + 2m Drop rating
- + Heavy-duty stainless-steel pocket clip
- + Meets the requirements for NFPA-1971-8.6 (2013)

### SUITABLE FOR

- + Emergency services
- + Utility maintenance
- + Tradespeople
- + Airports
- + Security
- + Factory
- + Recovery
- + Hazardous locations



sales@eskosafety.com

0800 500 470

56 Hurlstone Drive, New Plymouth

# esko®